

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.12.2014

Version number 21

Revision: 02.12.2014

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name:** ProMATIC® STONECHIP AEROSOL WHITE 500 ML
- **Article number:** SCW500
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Preparation
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
ProMATIC  
Second Avenue  
Chatham  
Kent  
ME4 5AU  
Tel: +44 (0)1634 823900  
Fax: +44 (0)1634 823909  
Email: info@capellasolutionsgroup.com
- **Further information obtainable from:** QHSE Department
- **1.4 Emergency telephone number:**  
Tel: +44(0) 1634 823900 (08.00 / 17.00)  
  
+31 629058130 (24 h/d, 7 d/wk)

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.  
 Eye Irrit. 2 H319 Causes serious eye irritation.  
 Skin Sens. 1 H317 May cause an allergic skin reaction.  
 STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xi; Sensitising

R43: May cause sensitisation by skin contact.



F+; Extremely flammable

R12: Extremely flammable.

R52/53-66-67: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

(Contd. on page 2)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.12.2014

Version number 21

Revision: 02.12.2014

**Trade name: ProMATIC® STONE CHIP WHITE 500 ML**

(Contd. of page 1)

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Warning! Pressurised container.

Has a narcotising effect.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** *Danger*

· **Hazard-determining components of labelling:**

*n*-butyl acetate

Rosin

butanone

ethyl acetate

· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P102 Keep out of reach of children.

P260 Do not breathe spray.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local regulations.

· **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

(Contd. on page 3)

GB



































**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.12.2014

Version number 21

Revision: 02.12.2014

**Trade name: ProMATIC® STONE CHIP WHITE 500 ML**

		(Contd. of page 2)
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane  F+ R12 -----  Flam. Gas 1, H220  Press. Gas C, H280	12.5-20%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate R10-66-67 -----  Flam. Liq. 3, H226  STOT SE 3, H336	12.5-20%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane  F+ R12 -----  Flam. Gas 1, H220  Press. Gas C, H280	5-10%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43-xxxx	butanone  Xi R36  F R11 R66-67 -----  Flam. Liq. 2, H225  Eye Irrit. 2, H319; STOT SE 3, H336	5-10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	isobutane  F+ R12 -----  Flam. Gas 1, H220  Press. Gas C, H280	5-10%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46-xxxx	ethyl acetate  Xi R36  F R11 R66-67 -----  Flam. Liq. 2, H225  Eye Irrit. 2, H319; STOT SE 3, H336	5-10%
CAS: 64742-49-0 EC number: 920-750-0 Index number: 649-328-00-1 Reg.nr.: 01-2119475133-43-xxxx	Naphtha (petroleum), hydrotreated light (< 0,1 % benzol CAS nr. 71-43-2)  Xn R65  Xi R38  F R11  N R51/53 R67 -----  Flam. Liq. 2, H225  Asp. Tox. 1, H304  Aquatic Chronic 2, H411  Skin Irrit. 2, H315; STOT SE 3, H336	2.5-5%
CAS: 64742-95-6 EINECS: 265-199-0 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35-xxxx	Solvent naphtha (petroleum), light arom. (< 0,1 % benzol CAS nr. 71-43-2)  Xn R65  Xi R37  N R51/53 R10-66-67 Carc. Cat. 2, Muta. Cat. 2 -----  Flam. Liq. 3, H226  Asp. Tox. 1, H304  Aquatic Chronic 2, H411  STOT SE 3, H335-H336	2.5-5%

(Contd. on page 4)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.12.2014

Version number 21

Revision: 02.12.2014

Trade name: **ProMATIC® STONE CHIP WHITE 500 ML**

		(Contd. of page 3)
CAS: 8050-09-7 EINECS: 232-475-7 Index number: 650-015-00-7 Reg.nr.: 01-2119480418-32-xxxx	Rosin ☒ Xi R43 ☠ Skin Sens. 1, H317	2.5-5%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32-xxxx	xylene ☒ Xn R20/21 ☒ Xi R38 R10 ☠ Flam. Liq. 3, H226 ☠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	1-2.5%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

#### **SECTION 4: First aid measures**

- **4.1 Description of first aid measures**
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

#### **SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

#### **SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Ensure adequate ventilation  
Keep away from ignition sources.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

#### **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.12.2014

Version number 21

Revision: 02.12.2014

Trade name: ProMATIC® STONE CHIP WHITE 500 ML

(Contd. of page 4)

· **Information about fire - and explosion protection:**

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Protect from heat and direct sunlight.

· **7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

· **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**123-86-4 n-butyl acetate**

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm

Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

**106-97-8 butane**

WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm

Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm

Carc (if more than 0.1% of buta-1.3-diene)

**78-93-3 butanone**

WEL Short-term value: 899 mg/m<sup>3</sup>, 300 ppm

Long-term value: 600 mg/m<sup>3</sup>, 200 ppm

Sk, BMGV

**141-78-6 ethyl acetate**

WEL Short-term value: 400 ppm

Long-term value: 200 ppm

**8050-09-7 Rosin**

WEL Short-term value: 0.15 mg/m<sup>3</sup>

Long-term value: 0.05 mg/m<sup>3</sup>

Sen

**1330-20-7 xylene**

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm

Long-term value: 220 mg/m<sup>3</sup>, 50 ppm

Sk; BMGV

· **Ingredients with biological limit values:**

**78-93-3 butanone**

BMGV 70 µmol/L

Medium: urine

Sampling time: post shift

Parameter: butan-2-one

**1330-20-7 xylene**

(Contd. on page 6)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.12.2014

Version number 21

Revision: 02.12.2014

**Trade name: ProMATIC® STONE CHIP WHITE 500 ML**

(Contd. of page 5)

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· **Respiratory protection:** Not required.

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Not required.

**SECTION 9: Physical and chemical properties**

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Aerosol

Colour: According to product specification

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

· **Flash point:** < 0 °C (< 32 °F)  
Not applicable, as aerosol.

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 365 °C (689 °F)

· **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 7)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.12.2014

Version number 21

Revision: 02.12.2014

Trade name: ProMATIC® STONE CHIP WHITE 500 ML

(Contd. of page 6)

· <b>Explosion limits:</b>	
Lower:	1.2 Vol %
Upper:	10.9 Vol %
· <b>Vapour pressure at 20 °C (68 °F):</b>	3500 hPa (2625 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	0.839 g/cm <sup>3</sup> (7.001 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not applicable.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
Dynamic:	Not determined.
Kinematic:	Not determined.
· <b>Solvent content:</b>	
Organic solvents:	69.2 %
· <b>EU-VOC:</b>	580.4 g/l
· <b>EU-VOC in %:</b>	69.18 %
· <b>Solids content:</b>	37.1 %
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

**123-86-4 n-butyl acetate**

Oral	LD50	10770 mg/kg (rat)
Dermal	LD50	>17600 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>21.0 mg/m <sup>3</sup> (rat)

**106-97-8 butane**

Inhalative	LC50 / 4 h	658000 mg/m <sup>3</sup> (rat)
------------	------------	--------------------------------

**78-93-3 butanone**

Oral	LD50	2737 mg/kg (rat)
Dermal	LD50	6480 mg/kg (rabbit)
Inhalative	LC50 / 4 h	34 mg/m <sup>3</sup> (rat)

**141-78-6 ethyl acetate**

Oral	LD50	5620 mg/kg (rabbit)
------	------	---------------------

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.12.2014

Version number 21

Revision: 02.12.2014

**Trade name: ProMATIC® STONE CHIP WHITE 500 ML**

(Contd. of page 7)

Dermal	LD50	>18000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	1600 mg/m <sup>3</sup> (rat)
<b>64742-49-0 Naphtha (petroleum), hydrotreated light (&lt; 0,1 % benzol CAS nr. 71-43-2)</b>		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2600 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>193 mg/m <sup>3</sup> (rat)
<b>64742-95-6 Solvent naphtha (petroleum), light arom. (&lt; 0,1 % benzol CAS nr. 71-43-2)</b>		
Oral	LD50	3592 mg/kg (rat) (OECD401)
Dermal	LD50	>3160 mg/kg (rab) (OECD402)
Inhalative	LC50 / 4 h	>6193 mg/m <sup>3</sup> (rat)
<b>1330-20-7 xylene</b>		
Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	22.1 mg/m <sup>3</sup> (rat)

- **Primary irritant effect:**

- **on the skin:** No irritant effect.

- **on the eye:** No irritating effect.

- **Sensitisation:** Sensitisation possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

## SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

<b>123-86-4 n-butyl acetate</b>	
EC50 / 48 h	44 mg/l (daphnia magna)
EC50 / 96 h	320 mg/l (algae)
LC50 / 24 h	205 mg/l (daphnia magna)
LC50 / 96 h	18 mg/l (Pimephales promelas)
<b>141-78-6 ethyl acetate</b>	
EC50 / 24 h	2500 mg/l (daphnia magna)
<b>64742-49-0 Naphtha (petroleum), hydrotreated light (&lt; 0,1 % benzol CAS nr. 71-43-2)</b>	
LC50	127-159 mg/l (Leuciscus idus)
<b>64742-95-6 Solvent naphtha (petroleum), light arom. (&lt; 0,1 % benzol CAS nr. 71-43-2)</b>	
EC50 / 24 h	150 mg/l (daphnia magna)
EC50 / 48 h	7.4 mg/l (daphnia magna)
LC50 / 96 h	3.77 mg/l (fish)
<b>1330-20-7 xylene</b>	
EC50 / 48 h	7.4 mg/l (daphnia magna)
LC50 / 96 h	13.5 mg/l (fish)

- **12.2 Persistence and degradability** No further relevant information available.

- **12.3 Bioaccumulative potential** No further relevant information available.

- **12.4 Mobility in soil** No further relevant information available.

- **Ecotoxicological effects:**

- **Remark:** Harmful to fish

(Contd. on page 9)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.12.2014

Version number 21

Revision: 02.12.2014

Trade name: ProMATIC® STONE CHIP WHITE 500 ML

(Contd. of page 8)

- **Additional ecological information:**
- **General notes:**  
Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
Danger to drinking water if even extremely small quantities leak into the ground.  
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations


- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **European waste catalogue**

08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances
15 01 04	metallic packaging

- **Uncleaned packaging:**
- **Recommendation:** Non contaminated packagings may be recycled.

### SECTION 14: Transport information


- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR** 1950 AEROSOLS
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable
- **14.3 Transport hazard class(es)**
- **ADR**



- **Class** 2 5F Gases.
  - **Label** 2.1

---

- **IMDG, IATA**



- **Class** 2.1
  - **Label** 2.1

- **14.4 Packing group**
- **ADR, IMDG, IATA** Void
- **14.5 Environmental hazards:**
- **Marine pollutant:** No
- **14.6 Special precautions for user** Warning: Gases.

(Contd. on page 10)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.12.2014

Version number 21

Revision: 02.12.2014

Trade name: ProMATIC® STONE CHIP WHITE 500 ML

(Contd. of page 9)

· <b>Danger code (Kemler):</b>	-
· <b>EMS Number:</b>	F-D,S-U
· <b>14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	
· <b>Limited quantities (LQ)</b>	IL
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>Transport category</b>	2
· <b>Tunnel restriction code</b>	D
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	IL
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>UN "Model Regulation":</b>	UN1950, AEROSOLS, 2.1

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
No further relevant information available.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- R10 Flammable.
- R11 Highly flammable.
- R12 Extremely flammable.
- R20/21 Harmful by inhalation and in contact with skin.
- R36 Irritating to eyes.
- R37 Irritating to respiratory system.
- R38 Irritating to skin.
- R43 May cause sensitisation by skin contact.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 11)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.12.2014

Version number 21

Revision: 02.12.2014

**Trade name: ProMATIC® STONE CHIP WHITE 500 ML**

(Contd. of page 10)

R67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:** R&D legislation and regulatory advisor

· **Contact:** QHSE Department

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Gas 1: Flammable gases, Hazard Category 1

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas C: Gases under pressure: Compressed gas

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

· **\* Data compared to the previous version altered.**

GB